

UNIT INFORMATION

SSB UNIT		DSB UNITS		3/16" UNITS		1/4" UNITS	
3/16" SPACER	3/8"	DSB	7/16"	3/16" SPACER	9/16"	3/16" SPACER	11/16"
7/32" SPACER	7/16"	7/32" SPACER	1/2"	7/32" SPACER	5/8"	7/32" SPACER	3/4"
9/32" SPACER	1/2"	9/32" SPACER	9/16"	9/32" SPACER	11/16"	9/32" SPACER	13/16"
11/32" SPACER	9/16"	11/32" SPACER	5/8"	11/32" SPACER	3/4"	11/32" SPACER	7/8"
13/32" SPACER	5/8"	13/32" SPACER	11/16"	13/32" SPACER	13/16"	13/32" SPACER	15/16"
15/32" SPACER	11/16"	15/32" SPACER	3/4"	15/32" SPACER	7/8"	15/32" SPACER	1"
17/32" SPACER	3/4"	17/32" SPACER	13/16"	17/32" SPACER	15/16"	17/32" SPACER	1-1/16"
19/32" SPACER	13/16"	19/32" SPACER	7/8"	19/32" SPACER	1"	19/32" SPACER	1-1/8"
21/32" SPACER	7/8"	21/32" SPACER	15/16"	21/32" SPACER	1-1/16"	21/32" SPACER	1-3/16"
23/32" SPACER	15/16"	23/32" SPACER	1"	23/32" SPACER	1-1/8"	23/32" SPACER	1-1/4"
25/32" SPACER	1"	25/32" SPACER	1-1/16"	25/32" SPACER	1-3/16"	25/32" SPACER	1-5/16"
UP TO 10 SQ. FT.		UP TO 18 SQ. FT.		UP TO 36 SQ. FT.		UP TO 50 SQ. FT.	

**MUNTINS MAY
TOUCH GLASS ON
THESE OVERALLS**

AVAILABLE SPACERS:
METAL - ALUMINUM-
 BRONZE
SUPER SPACER -
 ALUMINUM GRAY-
TRISEAL -
 ALUMINUM GRAY

ALL UNITS OVER 50 SQ. FT. MUST BE TEMPERED

UNITS ARE MANUFACTURED USING AN ALUMINUM SPACER THAT HAS ALL FOUR CORNERS BENT AND IS JOINED WITH A STRAIGHT KEY. SPACER BENDING ENSURES THAT ALL CORNERS ARE CLOSED, THUS CREATING A BETTER SEAL. THE PRIMARY SEAL CONSISTS OF POLYISOBUTYLENE (PIB) ON THE SPACER. THE SECONDARY SEAL CONSISTS OF POLYURETHANE, A WELL-TESTED, HIGHLY RESPECTED SEAL. UNITS THAT FALL WITH IN THE SIZE LIMITATIONS ARE WARRANTED FOR 10 YEARS AND IGCC CERTIFIED. REFER TO UPG'S WARRANTY FOR MORE INFORMATION.

**THE SPACER IS TOO
THIN FOR US TO
DRILL AN ARGON
HOLE IN THE 3/16",
7/32" AND 9/32"
SPACERS.**

UPG-1 2023